GET STARTED AND EXPAND IN MANY WAYS

Access Point 2

HmIP-HAP2 | HmIP-HAP2-A

The Access Point 2 offers comfortable set-up and control of the Homematic IP system using an intuitive app. The device connects all Homematic IP devices via the free cloud.





Simple installation:

- 1. Connect to the router
- 2. Establish power-supply
- 3. Scan the QR code

Done 🗸

The Access Point offers the right solution for every smart home:

- Extension of the wireless range by integrating an additional Access Point
- Controlling several Access Points in different installations (e.g. for a holiday home) via one app
- Up to 15 users in each Homematic IP installation
- Extension and combination of the installation with Homematic IP Wired devices possible via the Homematic IP Wired Access Point

EASY AND INTUITIVE SET-UP

The Access Point is supplied with power and connected to a standard router. That's it!

By connecting Homematic IP devices, a comprehensive smart home system can be individually established

Set-up and control of devices is carried out using the free app with intuitive user guidance.

CONTROL YOUR SMART HOME FROM ANYWHERE

The app automatically enables access to the smart home system via the cloud at any time, even while vou are on the move.

HIGH SECURITY ACCORDING TO GERMAN QUALITY STANDARDS

- ✓ The Access Point reliably detects radio interference in the installation and warns in case of interference
- ✓ AES 128 encryption between devices, app and cloud
- ✓ Server location in Germany
- ✓ Secure use without registration
- ✓ Reliable radio protocol based on 868,3/869.525 MHz

VOICE CONTROL FOR YOUR SMART HOME

A large number of the Homematic IP devices and system functions offers comfortable voice control using Amazon Alexa or Google Assistant.

EASY AND FLEXIBLE INSTALLATION

The Access Point is operated either lying on a table or permanently mounted on the wall. The screws and plugs for installation are delivered with the device.

TECHNICAL SPECIFICATIONS

Supply voltage 5 V

Plug-in mains adapter (input) 100 V-240 V/50 Hz

2.5 W max

165 a

400 m

10/100 MBit/s, Auto-MDIX

Power consumption plug-in mains adapter

Current consumption 500 mA max.

Standby power consumption < 1 W

Degree of protection IP20

Ambient temperature 5 to 35 °C

Dimensions (W x H x D) 104 x 104 x 40 mm

Weight

Radio frequency band 868.0-868.6 MHz 869.4-869.65 MHz

Typ. open area RF range

Network

LOGISTICAL DATA

 Version
 White
 Anthracite

 Product reference
 161314A0
 161345A0

 EAN code
 4047976613144
 4047976613458

 Short description
 HmIP-HAP2
 HmIP-HAP2-A

Packing unit 32

Packing dimensions 184 x 140 x 73 mm

Weight incl. packaging 510 g

PACKAGE CONTENTS

Homematic IP Access Point 2

Plug-in mains adapter

Network cable

Mounting material (screws and plugs)

User manual