



- 5.0 Mp resolution
- High sensitivity with Starvis technology
- IK10 rating
- ONVIF 2.4 protocol support
- Smart functions support
- Support mobile monitoring: iOS & Android
- Ability to work with Partizan Cloud Storage
- Remote access to the device with Partizan MAC

Your manual is here:

<http://manuals.partizan.global>



Partizan software:

<http://apps.partizan.global>



IP Camera		
Model	IPD-5SP	
Version	VP Cloud v1.1	
SKU	2521	
Image Sensor		
Sensor	1/2.8" Sony Starvis Starlight	
Pixel Size, µm	2.0x2.0	
Resolution, pixels@fps	Mainstream (max)*	PAL: 2592x1944@25, 2560x1440@25, 1920x1080@25, NTSC: 2592x1944@30, 2560x1440@30, 1920x1080@30
	Substream (max)*	PAL: 800x448@25, NTSC: 800x448@30
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux	0.0001	
Dynamic range WDR, dB	72	
S/N ratio, dB	48	
Video functions	AES, AGC, AWB, BLC, OSD, PrivacyMasks	
Smart functions	Human detection, Face detection (more functions when using together with Cloud-series NVR)	
Codec profile	H.264/H.265	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	128-8192
	Variable	Worst/Worse/General/Good/Better/Best
<b>*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream</b>		
Lens		
Focal length, mm	2.8	
Iris, F	1.2	
Angle of View, °	Horizontal	91
	Vertical	75
Lens Type	Aspherical	-
	Spherical	+
Lens mount	M12	
Control, Manual/Auto	+/-	
IR LED		
Distance, m	-	
Number of LEDs, pcs.	-	
Beam Spread, °	-	
Wavelength, nm	-	
IR Cut Filter, Manual/Auto	-	
Network		
Network interface	RJ-45 (10/100Base-T)	
Network functions	Cloud/NiP/DDNS/IPFilter/E-mail/NTP/UPNP/FTP/RTSP	
Languages supported	English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech	
Default IP address	<b>DHCP (Auto)</b>	
Username	<b>admin</b>	
Password	<b>admin</b>	
HTTP port	80	
ONVIF port	8899	
RTSP port	554	
RTSP string	rtsp://IPAddress:port/user=admin&password=admin&channel=1&stream=0.sdp?	
Snapshot capture link	http://IPAddress/webcapture.jpg?command=snap&channel=1&user=admin&password=admin	
Control port	34567	
Configuration software	Partizan (Setup Tool), Partizan Device Manager	
Monitoring program	Partizan	
Mobile software (support)	Partizan	
Protocol integration	Partizan SDK, ONVIF 2.4+	
Dimensions		
Size, mm	Total length	62
	Housing	Ø120x62
	Bracket	-
Weight, g	360	
Common		
Power Supply	DC12V, A	0.3
	PoE Class/W	0/6
Alarm	Inputs	-
	Outputs	-
Audio	Built-in microphone	-
	Inputs	-
	Outputs	-
Memory card	-	
Housing material, plastic/metal	-/+	
Bracket material, plastic/metal	-	
IP rating	44	
IK rating	10	
Operating temperature, °C	+10 - +50	
Warranty, years	3	