



- Wi-Fi IP camera
- 3.0 Mp resolution
- IP66 rating
- IR LED
- 3-Axis mounting
- ONVIF 2.4 protocol support

Your manual is here:
<http://manuals.partizan.global>



Partizan software:
<http://apps.partizan.global>



IP Camera		
Model	IPO-2SP	
Version	Kit v2.1	
SKU	2761	
Image Sensor		
Sensor	1/2.7" Full HD CMOS	
Pixel Size, µm	2.8x2.8	
Resolution, pixels@fps	Mainstream (max)*	PAL: 3Mp@12 2Mp@12, 1.3Mp@12, 1Mp@12 NTSC: 3Mp@12 2Mp@12, 1.3Mp@12, 1Mp@12
	Substream (max)*	PAL: 640x480@12, 320x240@12 NTSC: 640x480@120, 320x240@12
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux	0.01	
Dynamic range WDR, dB	72	
S/N ratio, dB	48	
Video functions	AEC, AGS, AWB, ABF, BLC, OSD, PrivacyMasks	
Smart functions	Human detection	
Codec profile	H.264/H.265	Baseline / Main / High
Exposure mode, s	Auto	1/25-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm	3.6	
Iris, F	1.4	
Angle of View, °	Horizontal	77
	Vertical	61
Lens Type	Aspherical	-
	Spherical	+
Lens mount	M12	
Control, Manual/Auto	-	
IR LED		
Distance, m	≤30	
Number of LEDs, pcs.	3 array LED	
Beam Spread, °	60	
Wavelength, nm	850	
IR Cut Filter, Manual/Auto	-/+	
Network		
Network Interface	RJ-45 (10/100Base-T)	
Wireless LAN	Standard	802.11(b/g/n)
	Frequency, Ghz	2.4
	Max. wireless power, mW	<100
Network functions	Cloud/NIP/DDNS/IPFilter/E-mail/NTP/UPNP/RTSP	
Languages supported	English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech	
Default IP address	DHCP (Auto)	
Username	admin	
Password	admin	
HTTP port	80	
ONVIF port	8899	
RTSP port	554	
RTSP string	rtsps://IPaddress:port/user=admin&password=admin&channel=1&stream=0.sdp?	
Snapshot capture link	http://IPaddress/webcapture.jpg?command=snap&channel=1&user=admin&password=admin	
Control port	34567	
Configuration software	Partizan (Setup Tool), Partizan Device Manager	
Monitoring program	Partizan	
Mobile software (support)	Partizan	
Protocol integration	Partizan SDK, ONVIF 2.4+	
Dimensions		
Size, mm	Total length	175
	Housing	Ø62x100
	Bracket	Ø57x75
Weight, g	470	
Common		
Power Supply	DC12V, A	0.5
	PoE Class/W	-
Alarm	Inputs	-
	Outputs	-
Audio	Built-in microphone	-
	Inputs	-
	Outputs	-
Memory card	-	
Accessories	-	
Housing material, plastic/metal	-/+	
Bracket material, plastic/metal	-/+	
IP rating	66	
IK rating	-	
Operating temperature, °C	-40 - +60	
Warranty, years	3	