



- 8.0 Mp resolution
- IP66 rating
- IR leds
- PoE support
- 3-Axis mounting
- ONVIF 2.6 protocol support

IP Camera		
Model		IPD-5SP-IR
Version		4K 1.0
Image Sensor		
Sensor		1/2.3" OmniVision 4K
Pixel Size, µm		1.62x1.62
Resolution, points@fps	Main stream	PAL:3840x2160@15, 2592x1520@18, 1920x1080@25 NTSC:3840x2160@15, 2592x1520@18, 1920x1080@30
	Sub stream	PAL:1920x1080@25, 1280x720@25, 640x480@25 NTSC:1920x1080@30, 1280x720@30, 640x480@30
Day/Night mode		Auto/Color/Black&White
Sensitivity, Lux/Iris		0.01
Dynamic range WDR, dB		72
S/N ratio, dB		48
Video functions		AES, AGC, AWB, BLC, OSD, PrivacyMasks
Smart functions		-
Codec profile	H.264/H.265	Baseline / Main / High
	Auto	1/5-1/20000
Exposure mode, s	Manual	1/5-1/20000
	Constant	256-16384
Bitrate Type, kb/s	Variable	Worst/Worse/General/Good/Better/Best
Lens		
Focal length, mm		3.6
Iris, F		1.4
Angle of View, °	Horizontal	96
	Vertical	81
lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control		-
IR LED		
Distance, m		Up to 30
Number of LEDs, pcs.		1, Array LED
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter		Auto
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		DDNS/IPFilter/E-mail/NTP/PPPoE/UPNP/FTP/RTSP
Languages supported		English
Default IP address		DHCP (Auto)
Username		admin
Password		admin
HTTP port		80
ONVIF port		80
RTSP port		554
RTSP string	Main stream	rtsp://ip:port/Ch01/0
	Sub stream	rtsp://ip:port/Ch01/1
Control port		9988
Configuration software		Web interface, IE
Monitoring program		Partizan CMS
Mobile software(support)		-
Protocol integration		ONVIF 2.6+
Dimensions		
Size, mm	Total length	89.9
	Housing	Ø126.6x89.9
	Bracket	-
Weight, g		375
Common		
Power Supply	DC12V, A	0.5
	PoE, Class/W	0/6
Alarm	Inputs	-
	Outputs	-
Audio	Inputs	-
	Outputs	-
Memory card		-
Housing material		Metal
Bracket material		-
IP rating		66
IK rating		-
Operating temperature, °C		-40 - +60
Warranty, years		3