



Smoke Alarm

Smoke and temperature monitoring for optimal fire detection

With the Smoke Alarm from Develco Products, your customers will never have to worry about fire or smoke in their homes again, making the Smoke Alarm essential for insurtech, security, or home care solutions.

While at home, the Smoke Alarm will warn your customer about smoke, using a loud sound. By connecting several Smoke Alarms distributed in different places of the home, customers can hear the alarm of a fire in the basement while they are on the top floor.

While away, your customer will be instantly notified through an internet-connected gateway. No matter whether the user is at work, visiting friends and family or on holiday, the Smoke Alarm keeps them informed regardless of their location.

Key features are:

- Smoke sensor - IAS Zone
- Temperature sensor
- European certification
- Zigbee certified

The Smoke Alarm can also notify the user when the battery gets low ensuring the Smoke Alarm is not running out of power and preventing the alarm from going off at night due to low battery status. Through your IoT system, a Smoke Alarm can be connected to other intelligent devices. For instance, smart lighting can be set to flash in cases of smoke detection.

Moreover, the Smoke Alarm will report the status and temperature every two minutes via the customer's smart home system. The wireless Smoke Alarm is battery powered and easily mounted to the ceiling with the included screws.



- **Easy installation**
- **3 years+ battery lifetime**
- **Diameter 65 mm**



Smoke Alarm - Technical specifications

Model number: SMSZB-120

General

Dimensions (Ø x H) Ø 65 x 40 mm

Color White

Power supply Battery: 1 x CR123, exchangeable
 Battery life: 3 years, reporting every 5 minutes
 Battery level and low battery warning can be reported

Radio Sensitivity: -98 dBm
 Output power: +8 dBm

Environment IP class: IP20
 Operation temperature 0 to +50°C
 Relative humidity 10-95% non-condensing

Functions

Smoke sensor Optical
 Siren output 85 dB/3m

Temperature sensor Range: 0 to +50°C
 Resolution: 0.1°C (accuracy Typ ±0.5°C and Max ±2°C)
 Sample time: config.: 2 s -65,000 s
 Reporting: configurable

Communication

Wireless protocol Zigbee Home Automation
 Zigbee end-device

Certifications

Conforming to CE, RED and RoHS directives
 DIN EN 14604 and DIN 14676 certified
 Zigbee Home Automation 1.2 certified