



- 8.0 Mp resolution
- Smart functions support
- IP67 rating
- SD card support
- Built-in alarm red & blue flashing lights
- Built-in microphone and speaker
- IR + White LED + Smart Detection, 24/7 Full Colour
- 3-Axis mounting
- ONVIF 2.6 protocol support
- Partizan mobile app support
- Ability to work with Partizan Cloud Storage
- Remote access to the device with Partizan MAC

Your manual is here:

<http://manuals.partizan.global>



Partizan software:

<http://apps.partizan.global>



IP Camera		
Model	IPD-5SP-IR	
Version	4K FADA SH Black	
SKU	3529	
Image Sensor		
Sensor	1/2.7" CMOS	
Pixel Size, µm	2.0x2.0	
Resolution, pixels@fps	Mainstream (max)*	PAL: 8Mp@15 NTSC: 8Mp@15
	Substream (max)*	PAL: 2Mp@15 NTSC: 2Mp@15
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux	0.007	
Dynamic range WDR, dB	72	
S/N ratio, dB	48	
Video functions	DWDR, 3D DNR	
Smart functions	Smart Motion Detection (Pedestrian (Human)/Vehicle Detection), Perimeter Intrusion Detection, Line Crossing Detection	
Codec profile	H.264/H.265	Baseline / Main / High
Exposure mode, s	Auto	1/5-1/20000
	Manual	1/5-1/20000
Bitrate Type, kb/s	Constant	512-6144
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm	2.8	
Iris, F	1.0	
Angle of View, °	Horizontal	110
	Vertical	58
Lens Type	Aspherical	-
	Spherical	+
Lens mount	M12	
Control, Manual/Auto	-	
Night Vision Range		
Distance, m	≤20	
Number of LEDs, pcs.	1 IR LED + 2 White LED	
Beam Spread, °	60	
Wavelength, nm	850	
IR Cut Filter, Manual/Auto	-/+	
Network		
Network Interface	RJ-45 (10/100Base-T)	
Network functions	Partizan MAC protocol, TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, HTTPS	
Languages supported	English, Francais, Deutsch, Italiano, Portuguese, Russian, Spanish, Turkish	
Default IP address	DHCP (Auto)	
Username	admin	
Password	admin	
HTTP port	80	
ONVIF port	80	
RTSP port	554	
RTSP string	Main stream	rtsp://ip:port/Ch01/0
	Substream	rtsp://ip:port/Ch01/1
Snapshot capture link	http://[IP]:[Web PORT]/API/OnvifSnapshot/Get	
Control port	9988	
Configuration software	Partizan (Setup Tool), Web interface (IE)	
Monitoring program	Partizan	
Mobile software (support)	Partizan	
Protocol integration	ONVIF 2.6+ (Profile S, Profile G, Profile T)	
Dimensions		
Size, mm	Total length	78
	Housing	∅100x78
	Bracket	-
Weight, g	320	
Common		
Power Supply	DC12V, A	0.6
	PoE Class/W	0/8.3
Audio	Built-in microphone	+
	Built-in speaker	+
Alarm	Built-in red & blue flashing lights	
Memory card	Micro SD (≤256Gb)	
Housing material, plastic/metal	+/-	
Bracket material, plastic/metal	-	
IP rating	67	
IK rating	-	
Operating temperature, °C	-40 - +60	
Warranty, years	3	