

KNX-RF COMPATIBLE PRODUCTS

Universal dimmer RLC LED paladin 673 830 rf



Overview

- Universal dimmer for R,L,C and LED lamps
- Max. load 250W (halogen lamps with electronic transformer)
- Minimum dimming-value adjustable
- For leading or trailing edge dimming
- Additional input for wired push button
- RF-repeater function included
- Compact housing
- Flush-mounted fitting
- Protection class IP20
- KNX-RF compatible

Order numbers

■ **paladin**

673 830 rf Universal dimmer for
RLC & LED lamps

Technische Änderungen vorbehalten.

KNX-RF COMPATIBLE PRODUCTS

Universal dimmer RLC LED paladin 673 830 rf

Technical data

Supply voltage	230V ~50/60Hz
Power consumption	2,6 VA
Switching capacity	Halogen lamps with electronic transformer: up to 250W Halogen lamps with inductive transformer: up to 200W LED:4W...100W
Transmission type	Codified transmission in 868,4MHz with ERP>8mW and a coverage of 100m (in the free field)
Switching functions	Switching (ON/OFF) Dimming Set dimming value
Permitted ambient temperature	0°C...+40°C
Dimensions	46 x 46 x 30 mm
Mounting	Flush-mounting
Connection type	Screw-type terminal
Protection class	IP20

Technische Änderungen vorbehalten.

