ORNO®

LIVING **INNOVATIONS**

DATA SHEET

LED floodlight SIROCCO with motion sensor

symbol: OR-NL-348BLPPR4

The main features:

Use of the LED technology guarantees high energy efficiency and long life The protection level IP44 allows its installation in rooms of increased humidity The PIR motion detector responds to motion and the twilight sensor switches lighting on only if necessary (depending on settings) Built-in LED driver.

LIGHT SOURCE: LED SMD	RATED POWER: 25W	LUMINOUS FLUX: 1500lm	COLOUR TEMPERATURE: 4000K
PROTECTION RATING: IP44	Protection rating		

Technical specifications:

General Information

Power supply:	230V~, 50Hz
Light source:	LED SMD
Rated power:	25W
Colour rendering index (ra):	>85
Luminous flux:	1500lm
Colour temperature:	4000K
Protection rating:	IP44
Colour:	black

Dimensions (width x height x depth [mm]):	180 / 208 / 178
Control of the motion sensor :	✔ yes
Type of sensor:	PIR
Detection angle:	180 Grad
The range of motion detection:	12m
Adjustment of the light intensity (lux):	✔ yes
Light intensity adjustment range (lux):	<3—2000lux
Adjustment of lighting time (time):	✔ yes
Lighting time adjustment range (time) :	min: 10 sec. ± 3 sec.; max: 7 min. ± 2 min.
Adjustment of the range of motion detection (sens):	✘ no
Other features:	regulation of the floodlight's position: 45? horizontally, 135? vertically; regulation of the sensor's position: 180? horizontally, 90? vertically